

## Sortimentsübersicht SterlingOSB-Zero – baurechtlich zugelassen, formaldehydfrei verleimt

	Format [mm] (Deckmaße)	Dicke (mm)							
		9	12	15	18	22	25	30	
<b>OSB/2-Zero</b>	glattkantig	2440 x 1220	[X]	[X]	[X]	[X]			
		2070 x 2800		[X]	[X]	[X]			
<b>OSB/3-Zero</b>	glattkantig	2500 x 1250	[X]	[X]	[X]	[X]	[X]	[X]	
		2650 x 1250		[X]	[X]				
		2800 x 1250		[X]	[X]	[X]	[X]		
		3000 x 1250		[X]	[X]				
		5000 x 1250		•	X	X	X	•	
		5000 x 2500		•	X	X	X	•	
		2800 x 2070		X	X	X	X		
	Nut + Feder – 4-seitig	2500 x 675		[X]	(X)	(X)	(X)	X	[X]
	2500 x 1250		X	[X]	[X]	X	X		
<b>OSB/4-Zero</b>	glattkantig	2500 x 1250			[X]	[•]	[•]		
		2650 x 1250		X	X				
		2800 x 1250		X	X				
		3000 x 1250			X				
	Nut + Feder – 4-seitig	2500 x 1250			•	•	•	•	
	Nut + Feder – 2-seitig	5000 x 1230					[X]	[X]	

Sonderformate auf Anfrage; Mindestmenge ca. 150 m<sup>3</sup>

Einen Überblick über das Sortiment von SterlingOSB-Conti finden Sie in einer separaten Broschüre. • = auf Anfrage X = Lagerware [X] = PEFC [X] = FSC (X) = auf Anfrage zertifiziert